

PM102

Cold Planer

Compact size, maximum performance.



Good Weight Distribution

- Weight of engine and hydraulics positioned over the rotor
- Enhances cut; cleaner
- Better traction

Simple Operation

- Easy "one-man-operation" in locations that permit it
- Control surfaces within easy reach

Visibility

- Better operator and crew safety
- More precision
- Better control
- Rear camera option



High Mobility

- Exceptional maneuverability
- Compact size gets in tight spaces
- Good travel speed enables quick repositioning
- Available with track or wheel undercarriage

Exclusive Quick Release Conical Tool Holder

- Facilitates easy change of tools
- Ensures proper tool rotation
 - Longer tool life
 - Better cutting performance
- Helps protect rotor and rotor drive

Rotor Drive

- Rotor drive disengages when low rotor RPM is detected
- Minimizes drive system damage if rotor strikes immovable object
- Drive belt is easy to change



Base Block (welded to rotor mandrel)

Exclusive Quick Release
Conical Tool Holder

Cutting Tool



PM102 Cold Planer Specifications

Operating

Weight, Track undercarriage*	17 600 kg	38,810 lb
Weight, Wheel undercarriage*	17 100 kg	37,705 lb
Length	10.7 m	35' 1"
Maximum Width, (Track)	2.5 m	8' 2"
Maximum Width, (Wheel)	2.4 m	7' 9"
Machine Width, right rear leg tucked (Track)	1.98 m	6' 5"
Machine Width, right rear leg tucked (Wheel)	2.0 m	6' 6"
Maximum Height (with canopy)	3.4 m	11' 2"
Cutting Width	1000 mm	40"
Maximum Cutting Depth	305 mm	12"
Conveyor swing	41 degrees left or right of center	
Inside Turning Radius, (Track)	3.45 m	11' 3"
Inside Turning Radius, (Wheel)	3.45 m	11' 3"
Shipping Weight, Track undercarriage**	17 100 kg	37,705 lb
Shipping Weight, Wheel undercarriage**	16 400 kg	36,160 lb
Shipping Length (conveyor folded)	8.5 m	27' 8"
Shipping Maximum Height (canopy folded)	3.1 m	10' 1"

Cat® C7 Engine with ACERT™ Technology

Rated Power	168 kW	225 hp
Operating Speed, (Track)	27 mpm	89 fpm
Operating Speed, (Wheel)	46 mpm	151 fpm
Travel Speed (Track)	4.1 km/h	2.5 mph
Travel Speed (Wheel)	6.4 km/h	3.9 mph

Miscellaneous

Fuel Tank	400 L	105 gal
Water Spray System	1060 L	280 gal



Flush Cutting Capability

Wheel undercarriage option shown.

* Operating Weights are approximate and include coolant, lubricants, full fuel tank, full water tank and 75 kg (165 lb) operator.

** Shipping Weights are approximate and include coolant, lubricants, 50% fuel level, and empty water tank.

The Cat® Advantage - Single Source Provider

	Cat Dealer	Competitive Dealer	Comment
Convenient worldwide dealer locations	✓		More than our 5 largest competitors combined
Engine service	✓		Cat machines feature Cat engines
Machine service	✓	✓	
Service technician trained for paving equipment	✓		Cat technicians trained on Cat machines
24/7/365 parts availability on most service parts	✓		Long lead times for competitive OEM parts
New OEM parts	✓		Competition offers inferior aftermarket parts
Reconditioned OEM parts	✓		Rebuilt to OEM spec by Cat Reman
Available financing options	✓		Available through Cat Financial
Application expertise	✓		Personnel understand the paving business
Machine rental	✓		Keeps your capital expense low
Products with high resale value	✓		Durable Cat machines built to last

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

QEXQ1514 (01-11)

© 2011 Caterpillar
All Rights Reserved

Materials and specifications are subject to change without notice.
Featured machines in photos may include additional equipment.
See your Cat dealer for available options.

CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow," the "Power Edge" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

